

EIZO[®]


Raptor[®] | Re/Vue[™] | SafeGuard[™]



End-to-End ATC Visual System




ATC Visual System



The ATC Visual System

The ATC Visual systems consists of several graphics-related devices designed to transfer air traffic management video data to the controller. It is not uncommon for an ANSP to receive an integrated solution made up of multiple vendors' products, which can result in critical errors with compatibility and other issues that could risk program delays. EIZO's end-to-end ATC Visual System encompasses monitors, video encoders, dedicated graphics boards, and an upgradeable recording solution, all of which are designed and tested for interoperability from the outset.



DISPLAY

Smart Monitors

Raptor primary control monitors and high-brightness tower monitors are relied on by thousands of controllers in some of the world's most demanding ANSPs for the safe and efficient movement of air traffic. Both 2K x 2K and 4K x 2K formats are available to support varying installation requirements. See page 6-7


SMART TECHNOLOGIES

Raptor monitors feature EIZO's unique smart technologies which simplify installation and streamline operation. See page 4-5

CAPTURE

Encoding & Streaming

Re/Vue encoding & streaming solutions provide the accuracy needed for ATC, training & simulation, and command & control applications. They offer a true lossless compression ratio of 10,000:1 to 40,000:1 for typical ATC data - the highest in the industry. See page 8-9



MANAGE

Recording & Playback

SafeGuard is a data capture & content management solution designed to receive multiple feeds from communication interfaces employed in mission-critical ATC. It provides a highly secure archive supporting the management, analysis, and distribution of data for Post Incident Investigation, Search & Rescue Operations, Training & Performance Analysis, and Verification & Validation. See page 10-11




Make the Switch to a Smarter Monitor

Intelligent Display Platform

EIZO's Intelligent Display Platform (IDP) equipped in select Raptor monitors enables simultaneous display of video signals from up to four independent sources. Users have complete freedom to place each window anywhere on the screen.

Freely arrange each source window anywhere on the screen.





Actual Size

Scaled
(maintains aspect ratio)

Full Screen
(stretched)

Display up to four video sources simultaneously.




At-the-Glass Image Capture Built-In

The Raptor SQ2826 is the industry's first primary control monitor to feature truly built-in image capture at the glass. All displayed image content, including the monitor's OSD menu operations, is accurately output using the monitor's DVI (REC OUT) connection.


Last Frame Display

EIZO's unique Last Frame Display function automatically displays the last available frame displayed prior to any signal disruption accompanied by a text overlay of the status. This ensures the ATCO is immediately aware the disruption while providing the latest visual information as a reference until the issue is addressed.

Monitor loses picture when signal is disrupted.



Raptor monitor continues to show the last frame.



Integrated Switching

SwitchLink enables seamless switching of keyboard, mouse, and dynamic touch input without the need for an external KVM switch. Up to six workstations can be connected and operated by a single keyboard and mouse.



SwitchLink Mouse

Moving the cursor across each window will instantaneously and automatically switch workstation inputs.



SwitchLink Keyboard

Press a predefined hotkey to switch USB control of the keyboard and mouse to another workstation.



SwitchLink Dynamic Touch


With IDP displaying up to four workstations on a single monitor, SwitchLink enables each window to have its own independent touch connection. Simply touch the screen and the monitor will automatically switch to the target input. *Availability varies by model.*

Streamline Installation and Maintenance


With SwitchLink, video sources connect to the monitor directly, eliminating the need for a KVM switch.

- ✓ Reduce cabling and cable management
- ✓ Reduce power consumption and connection requirements
- ✓ Avoid compatibility issues

Traditional configuration using a KVM switch.



SwitchLink eliminates the need for a KVM switch.





6th Generation 2K x 2K Primary Control Monitor

The Raptor SQ2826 is the world's first 2K monitor for ATC to comply with 100 x 100 VESA mounting standards due to its light weight of just 9.2 kg. It features EIZO's unique smart technologies for streamlined installation and operation.

- ✓ World's 1st 2K x 2K monitor with VESA 100 x 100 compliance
- ✓ 28.1-inch with 2K x 2K (2048 x 2048)
- ✓ IDP, SwitchLink, At-the-Glass Image Capture, and Last Frame Display smart technologies
- ✓ 24/7 reliable operation

Light Weight
9.2 kg

VESA Mount Compliance
100 x 100mm



High-Brightness Tower Monitors

Raptor tower monitors provide optimal resolution and a wide brightness range for clarity in traditional or remote tower environments. Select models feature EIZO's smart technologies for streamlining installation and operation.



Minimum Brightness



Maximum Brightness

- ✓ 15 to 32-inch size screens
- ✓ Standard and high-brightness models
- ✓ Up to 4K x 2K (3840 x 2160) resolution
- ✓ PCAP touch panel models
- ✓ SwitchLink for select models
- ✓ 24/7 reliable operation

Industry's 1st 4K x 2K Primary Control Monitor for ATC

The Raptor RP4325 (42.5-inch) is the industry's first 4K x 2K primary control monitor developed specifically for ATC. Alongside it, the Raptor RP5525 (54.6-inch) offers an even more spacious option for viewing a large volume of control data on a single screen.

- ✓ 42.5 or 54.6-inch spacious screen
- ✓ 4K x 2K (3840 x 2160) resolution
- ✓ IDP, SwitchLink, and Last Frame Display smart technologies
- ✓ 24/7 reliable operation



Extensive Range of Auxiliary Monitors

EIZO's comprehensive line of auxiliary monitors provides control centers, towers, and training & simulation facilities with a wide range of monitor sizes and features sets to suit individual requirements.

- ✓ 15 to 37.5-inch size screens
- ✓ Wide and square formats available
- ✓ Resolutions of up to 3840 x 2160
- ✓ Eye care technologies
- ✓ Sustainable monitor build



...and more!

Industry-Leading Solutions

EIZO's Re/Vue products are encoding & streaming solutions developed for mission-critical ATC applications. They feature true lossless compression of 10,000:1 to 40,000:1 for typical ATC data – the highest in the industry.

- ✓ Synchronous encoding & streaming up to single or dual 4K (4096 x 2160)
- ✓ True lossless compression
- ✓ Platform and graphics card independent
- ✓ Fail-safe video bypass
- ✓ Fully compatible with Raptor SQ2826's At-the-Glass Image Capture function



Re/Vue Pro 2
Single channel with DisplayPort™



Re/Vue Pro 2 Max
Single channel with DisplayPort or DVI and audio connectors



Re/Vue Pro Duo
Dual channel with DisplayPort



Practical Application

Re/Vue can serve as standalone streaming devices or be seamlessly integrated as part of a broader recording solution.



Single and Dual Channel Encoding and Streaming

The Re/Vue lineup offers synchronous encoding & streaming of up to 4K x 2K with single or dual-channel support. This provides a range of solutions for ATC video data management to suit any configuration.





Single or Dual 4K x 2K



Single or Dual 2K x 2K



Other Configurations (Single or Dual)



Recording and Storage

SafeGuard captures audio, radar, At-the-Glass video signals, CCTV camera signals, and distributed network data. Content can be securely recorded to the SafeGuard server provided by EIZO for storage or playback and analysis.

Data Capture & Content Management

Secure End-to-End Solution

SafeGuard is an end-to-end solution comprising of software, servers, peripherals and other hardware components, and associated services entirely provided by EIZO. It is a turnkey solution that provides a highly secure archive supporting the management, analysis, and distribution of data from communication interfaces employed in mission-critical environments.

- ✓ Multi-format data capture and synchronous playback
- ✓ Highly secure browser-based management
- ✓ Centralized management and control
- ✓ User-defined roles and access rights



Synchronous Playback

SafeGuard achieves synchronous data playback of multiple channels from a user-specified time frame via browser-based client. Data is streamed from a secure server during playback so files do not need to be maintained on the local machine, alleviating storage space and streamlining data access between operating workstations.



Secure Browser-Based Management

SafeGuard's browser-based management employs HTTPS and enhanced authentication measures to ensure that all transactions between the browser client and data server are secure. Remote network access to the SafeGuard servers provides administrators with centralized control of data capture, system monitoring, and more for streamlined management.

ATC Visual System

EIZO's end-to-end ATC Visual System integrates smart monitors, encoding & streaming devices, data capture & content management software and servers, engineered for seamless interoperability across traditional and remote tower operations, control centers, and training facilities.



Specifications




Monitors

Raptor SQ2826



Raptor RP5525



Raptor RP4325




Raptor RP3226




Raptor RP2425



Raptor RP2126



Raptor RP1526



	Primary Control			Tower		Auxiliary	
Size	28.1" (71.2 cm)	54.6" (138.8 cm)	42.5" (108 cm)	32" (81.3 mm)	24.1" (61.2 cm)	21.3" (54.1 cm)	15" (38.1 cm)
Resolution	2048 x 2048	3840 x 2160	3840 x 2160	3840 x 2160	1920 x 1200	1600 x 1200	1024 x 768
Brightness Range	5 - 500 cd/m ²	20 - 700 cd/m ²	25 - 500 cd/m ²	30 - 350 cd/m ² (standard) 5 - 650 cd/m ² (high brightness)	10 - 750 cd/m ²	10 - 1000 cd/m ²	25 - 800 cd/m ²
Touch Panel	—	—	PCAP Available	PCAP Available	PCAP Available	PCAP Available	PCAP Available
Smart Technologies	IDP, SwitchLink, At-the-Glass Image Capture, Last Frame Display	IDP, SwitchLink, Last Frame Display	IDP, SwitchLink, Last Frame Display	SwitchLink (optional)	—	—	—
Input Terminals	DisplayPort x 2, DVI (dual link) x 2	DisplayPort x 2, DVI (dual link) x 2	DisplayPort x 2, DVI (dual link) x 2	DisplayPort x 2, HDMI x 2	DisplayPort, DVI, D-Sub mini 15 pin	DisplayPort, DVI-D (single link), D-Sub mini 15 pin	DisplayPort, DVI-D (single link), D-Sub mini 15 pin
Output Terminals	REC OUT	—	—	—	—	—	—
Weight*	9.2 kg	29.3 kg	20.5 kg	8 kg	9.2 kg	6.5 kg	3.4 kg
Mounting	Desktop, VESA, Panel, Chassis	VESA	Desktop, VESA	Desktop, VESA	Desktop, Tilt Stand, VESA	VESA, Custom Adapter Support	VESA

*Net weight for VESA version (without stand).
Some specifications vary between touch and non-touch models and optional technologies. For full specifications, visit www.eizoglobal.com/products/atc/
For EIZO's full lineup of FlexScan auxiliary monitors, visit www.eizoglobal.com/products/flexscan/



Encoders

Re/Vue Pro Duo



Re/Vue Pro 2 Max



Re/Vue Pro 2



	Dual Channel	Single Channel	
Video Compression Ratio*	10,000:1 to 40,000:1	10,000:1 to 40,000:1	10,000:1 to 40,000:1
Maximum Video Resolution	4096 x 2160 per channel (max. 2 channels)	DVI: 2048 x 2160 DisplayPort: 4096 x 2160	4096 x 2160
Video Connectors	DisplayPort (input and output) x 2	DisplayPort (input and output), Dual link DVI (input and output)	DisplayPort (input and output)
Audio Connectors	—	Stereo mini jack	—

*Actual compression ratio is dependent upon configuration parameters and video data type.



Software

SafeGuard



Multi-Format Data Capture and Playback	✓
Touch Screen Support	✓
Secure Browser-Based Management	✓
Intuitive User Interface	✓
User-Defined Roles and Access Rights	✓
Centralized Management and Control	✓
Highly Configurable	✓

For full specifications, visit www.eizoglobal.com/products/atc/

EIZO, the EIZO Logo, Raptor, Re/Vue, SafeGuard, and FlexScan are trademarks or registered trademarks of EIZO Corporation in Japan and other countries. SwitchLink is a registered trademark of EIZO Corporation in the United States and other countries. VESA is a registered trademark of the Video Electronics Standards Association in the United States and other countries. DisplayPort is a trademark of the Video Electronics Standards Association in the United States and other countries. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Copyright © 2025 EIZO Corporation. All rights reserved. (251205)

atc@eizo.com
<https://www.eizoglobal.com>

EIZO Corporation

153 Shimokashiwano, Hakusan, Ishikawa 924-8566 Japan
Phone +81-76-277-6792

EIZO Technologies GmbH

Benzweg 3, 82538 Geretsried, Germany
Phone : +49-8171-3492-0

EIZO Rugged Solutions

482 S. Keller Rd., Orlando, FL 32810
Phone: +1-407-262-7100